



LedKoning

GROEN PREMIUM LED STRIP

120
LEDS P/M



Groen






SPECIFICATIES


Dimbaar	Ja		
3M plakstrip over gehele lengte	Ja		
Garantie	2 jaar		
Op maat te knippen	12V: Elke 2,5 cm	24V: Elke 5 cm	
Aantal LED's p/m	120		
Type LED	2835 SMD		
Merk LED	Epistar		
Stralingshoek	120 graden		
Kleur	Groen		
Kleurtemperatuur (Kelvin)	-		
CRI	-		
Lichtsterkte (lumen) p/m	958 lm		
Aantal branduren	50.000		
Voltage (DC)	12V of 24V		
Watt - vermogen p/m	12W		
Bescherming	IP20		
Materiaal waterdichte bescherming (IP65/IP67)	Siliconen		
Achtergrond kleur strip (PCB)	Wit		
Plakstrip	IP20: 3M 300LSE	IP65: 3M VHB	IP67: 3M VHB
Breedte led strip	IP20: 8mm	IP65: 10mm	IP67: 10mm
Dikte led strip	IP20: 3mm	IP65: 6mm	IP67: 6mm
Aansluiting begin	5.5x2.1 DC stekker type vrouw		
Aansluiting einde	5.5x2.1 DC stekker type man		

TECHNISCHE TEKENINGEN


IP20 12V




IP65/67 12V



IP20 24V



IP65/67 24V



IP20



IP65




IP67





1M PREMIUM GROEN - 120 LEDS P/M



Color Parameters:

Chromaticity Coordinate: $x=0.1402$ $y=0.7101$ / $u'=0.0499$ $v'=0.5685$
 CCT=8425K (Duv=0.1642) Dominant WL:Ld =520.3nm Purity=75.3%
 Ratio:R=0.2% G=96.3% B=3.5% Peak WL:Lp=514.8nm FWHM=30.7nm
 Render Index:Ra=0.0 CRI=2.8

R1 =0 R2 =0 R3 =0 R4 =0 R5 =0 R6 =0 R7 =0
 R8 =0 R9 =0 R10=0 R11=0 R12=0 R13=0 R14=39 R15=0

Photo Parameters:

Flux = 957.7 lm Eff. : 80.19 lm/W Fe = 2.163 W

Electrical parameters:

V = 23.997 V I = 0.4977 A P = 11.94 W PF = 1.000
 LEVEL:OUT WHITE:OUT

Status: Integral T = 48 ms Ip = 50315 (77%)



CE CERTIFICAAT

AN XIN TESTING CERTIFICATION

Certificate of Conformity



Certification No. : ATT20092500368E
Applicant : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Manufacturer : Ledkoning
Address : Rietveldenweg 49D
 5222AP 's Hertogenbosch, The Netherlands
Product Description : 2835 LED Strip
 24K2835-05M1220,24K2835-05M1265,30K2835-05M1220,30K2835-05M1265
 65K2835-05M1220,65K2835-05M1265,24K2835-05M2420,24K2835-05M2465
 30K2835-05M2420,30K2835-05M2465,65K2835-05M2420,65K2835-05M2465
Model : RO2835-05M1220,RO2835-05M1265,RO2835-05M2420,RO2835-05M2465
 GR2835-05M1220,GR2835-05M1265,GR2835-05M2420,GR2835-05M2465
 BL2835-05M1220,BL2835-05M1265,BL2835-05M2420,BL2835-05M2465
 OR2835-05M1220,OR2835-05M1265,OR2835-05M2420,OR2835-05M2465
Trademark : N/A

The above products have been tested by us with listed standards and found in compliance with the Directive 2014/35/EU. It is possible to use CE marking to demonstrate the compliance with this Directive.

Test Standards	EN 55015: 2019
	EN 61547: 2009
	EN 61000-3-2:2019
	EN 61000-3-3: 2013+A1:2019

The certificate is based on a single evaluation of tested samples of above-mentioned product. It does not imply an assessment of the whole production and does not permit the use of the test laboratory logo.



Authorized Signer: _____
 Kevin Liu/Manager
 Sep. 27, 2020

Shenzhen An-Xin Testing Service Co., Ltd.
 Room 402-405, Floor 4th, Building C, Yuxing Technology Industrial Park, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China
 ☎ 86-0755-23009643 📠 86-0755-23009643 🌐 <http://www.anxinlab.com/>

Adres: Rietveldenweg 49D, 5222AP 's Hertogenbosch
 Tel: +3173 704 1100
 E-mail: info@ledkoning.nl
 Website: www.ledkoning.nl